

CAP EXTRUSION &
STANDARD COVER

GLASS (SEE NOTE)

CONT. ALUMINUM
EDGE COVER

SILICONE SEALANT & 80
DUROMETER SETTING
BLOCK ONE @ EACH END

OPEN CELL FOAM TAPE

EAVE EXTRUSION

1/4" WEEP SLOTS
(AS REQUIRED)

ALUMINUM FLASHING
(Ø5Ø)

SILICONE SEALANT

ROOFING & ROOF
FLASHING
(BY OTHERS)

INTERNAL CONNECTOR
W/ 1/4" F.H.S.S. BOLTS
(WELD CONNECTOR TO
BEARING PLATE)

BOLTS AS SIZED
BY ENGINEER

RAFTER
(4" EXTRUSION SHOWN)

1/4" CONT. ALUMINUM
BEARING PLATE

RUBBER ISOLATION PAD

STEEL STUD CURB
(BY OTHERS)

G.C. NOTE:
INTERIOR FINISH MUST NOT
BE INSTALLED PRIOR TO
SKYLIGHT INSTALLATION TO
ALLOW ACCESS TO S.S.
THRU-BOLTS.

1 EAVE DETAIL

SCALE: 1/2" = 1'-0"

NOTE:

- 1 3/16" INSULATED GLAZING SHOWN (THICKNESS & TYPE PER ARCHITECT AND ENGINEER)
- FLAT CURB CONSTRUCTION OF METAL STUDS (SHOWN), WOOD, STEEL, CONCRETE, OR ANY SURFACE CAPABLE OF WITHSTANDING LOADS APPLIED BY SKYLIGHT.
- VARIABLE SLOPE

EVERGREEN HOUSE

13645 N.E. 126th Place, Kirkland, WA 98034

(425) 821-1005 FAX (425) 823-5619

TYPICAL DETAILS

DRAWN BY: JJD

DRAWING NUMBER:

DATE: OCT. 11

T-1