

SILICONE SEALANT

CUSTOM ALUM. FLASHING  
(ONLY APPLICABLE IF  
REQUIRED BY SURROUNDING  
CONSTRUCTION)

ALUM. RIDGE FLASHING (Ø50)

CAP EXTRUSION &  
STANDARD COVER

SILICONE SEALANT

GLASS (SEE NOTE)

INTERNAL CONNECTOR  
W/ 1/4" Ø S.S. BOLTS  
(WELDED TO END R)

INTERNAL CONNECTOR  
W/ 1/4" Ø F.H.S.S. BOLTS  
(WELDED TO RAFTER)

1/4" CONTINUOUS ALUMINUM  
BEARING PLATE

RUBBER ISOLATION PAD

RIDGE TUBE (4" EXTRUSION SHOWN)  
(MODIFIED WITH BACK CUT-OUT)

BOLTS AS SIZED  
BY ENGINEER

## 5A CANOPY RIDGE DETAIL

SCALE: 1/2" = 1'-0"

### NOTE:

- 9/16" LAMINATED GLAZING SHOWN (THICKNESS & TYPE PER ARCHITECT AND ENGINEER)
- WALL CONSTRUCTION TO BE CAPABLE OF WITHSTANDING LOADS APPLIED BY SKYLIGHT.
- VARIABLE SLOPE

# EVERGREEN HOUSE

13645 N.E. 126th Place, Kirkland, WA 98034

(425) 821-1005 FAX (425) 823-5619

### CANOPY DETAILS

DRAWN BY: JJD

DRAWING NUMBER:

DATE: OCT. 11

## C-5A